



United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER OF PATENTS AND TRADEMARKS P.O. Box 1450 Alexandria, Vignia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	ATTORNEY DOCKET NO. CONFIRMATION NO.	
10/080,419	02/22/2002	Michael Stephen Bell	ERLG.P-021	ERLG.P-021 8270	
21121	7590 05/20/2003				
OPPEDAHL AND LARSON LLP P O BOX 5068 DILLON, CO 80435-5068			EXAMINER		
			EDWARDS, ANTHONY Q		
		•	ART UNIT	PAPER NUMBER	
			2835		
		•	DATE MAILED: 05/20/2003	DATE MAILED: 05/20/2003	

Please find below and/or attached an Office communication concerning this application or proceeding.

				Mc
	Applic	cation No.	Applicant(s)	
Office Action Summary		0,419	BELL ET AL.	
		ner	Art Unit	
		ny Q. Edwards	2835	
The MAILING DATE of this comm Period for Reply	unication appears on	the cover sheet with the	correspondence add	lress
A SHORTENED STATUTORY PERIOD THE MAILING DATE OF THIS COMMU - Extensions of time may be available under the provision after SIX (6) MONTHS from the mailing date of this color of the period for reply specified above, the maximum of the period for reply is specified above, the maximum of Failure to reply within the set or extended period for reply received by the Office later than three month earned patent term adjustment. See 37 CFR 1.704(b) Status	NICATION. ons of 37 CFR 1.136(a). In nomunication. (30) days, a reply within the a statutory period will apply are ply will, by statute, cause the as after the mailing date of thi	o event, however, may a reply be statutory minimum of thirty (30) d d will expire SIX (6) MONTHS fro application to become ABANDON	timely filed ays will be considered timely. the mailing date of this cor ED (35 U.S.C. § 133).	nmunication.
1) Responsive to communication(s)	filed on Preliminary	Amendment filed May 1	<u>13, 2003</u> .	
2a) ☐ This action is FINAL .	2b)⊠ This action	n is non-final.		
3) Since this application is in condit				merits is
closed in accordance with the pra	actice under <i>Ex part</i> e	e Quayle, 1935 C.D. 11,	453 O.G. 213.	
4)⊠ Claim(s) <u>1-5 and 7-11</u> is/are pend	ling in the application	n.		
4a) Of the above claim(s) is	/are withdrawn from	consideration.		
5) Claim(s) is/are allowed.				
6)⊠ Claim(s) <u>1-5 and 7-11</u> is/are rejec	ted.			
7) Claim(s) is/are objected to.		•		
8) Claim(s) are subject to rest Application Papers	riction and/or electio	n requirement.		
9)☐ The specification is objected to by	the Examiner.			
10)⊠ The drawing(s) filed on <u>26 June 20</u>	<u>02</u> is/are: a) <u>□</u> accep	oted or b) objected to by	the Examiner.	
Applicant may not request that any o	objection to the drawing	g(s) be held in abeyance.	See 37 CFR 1.85(a).	
11) The proposed drawing correction fi	led on is: a)[] approved b)∏ disapp	roved by the Examine	r.
If approved, corrected drawings are	required in reply to this	office action.		
12) The oath or declaration is objected	to by the Examiner.			
Priority under 35 U.S.C. §§ 119 and 120				
13) Acknowledgment is made of a cla	im for foreign priority	under 35 U.S.C. § 119	(a)-(d) or (f).	
a) ☐ All ·b) ☐ Some * c) ☐ None of	:. ·			
 Certified copies of the priori 	ty documents have b	peen received.		
Certified copies of the priori	ty documents have t	peen received in Applica	ition No	
3. Copies of the certified copieapplication from the Inte* See the attached detailed Office ac	ernational Bureau (Po	CT Rule 17.2(a)).	•	Stage
14)⊠ Acknowledgment is made of a claim	n for domestic priority	y under 35 U.S.C. § 119	(e) (to a provisional	application).
a) $igtimes$ The translation of the foreign 15) $igcap$ Acknowledgment is made of a clair	• • •			
Attachment(s)				
 Notice of References Cited (PTO-892) Notice of Draftsperson's Patent Drawing Review Information Disclosure Statement(s) (PTO-1449) 			ary (PTO-413) Paper No(s il Patent Application (PTC inuation Sheet .	
J.S. Patent and Trademark Office				

Continuation of Attachment(s) 6). Other: marked up copy of Fig. 4 of U.S. Pat. No. 6,282,087.

DETAILED ACTION

Drawings

The drawings are objected to as failing to comply with 37 CFR 1.84(p)(4) because reference character "124" has been used to designate both the "rail" in FIG. 2 and the "bottom rail" in FIG. 4. A proposed drawing correction or corrected drawings are required in reply to the Office action to avoid abandonment of the application. The objection to the drawings will not be held in abeyance.

Claim Objections

Claims 5-7, 10 and 11 are objected to because of the following informalities: each claim recites the limitation(s) "barriers disposed at at least third and forth locations along the first direction, the third location closer to the first connector than the second location" in the preamble of the method claims. There is insufficient antecedent basis for this limitation in the claim. It is noted that "a plurality of first electrical connectors" is recited after "the first connector."

Likewise, the examiner contents that "the second location" should read "the forth location."

Appropriate correction is required.

Claim Rejections - 35 USC § 102

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

Claims 1, 2, 8 and 9 are rejected under 35 U.S.C. 102(e) as being anticipated by U.S. Patent No. 6,282,087 to Gibbons et al. Referring to claim 1, Gibbons et al. disclose a computer

Art Unit: 2835

system, comprising an enclosure shaped (200) with a plurality of opposed pairs of first and second guides (216), the first guides all substantially coplanar within a first plane, the second guides all substantially coplanar within a second plane, each pair of guides defining a respective plane (204), the respective planes of the pairs of guides all parallel to each other, each pair of guides separated by a respective spacing, each pair of guides shaped to receive a respective planar carrier (206) by insertion in a first direction (see "z" direction of marked up FIG. 4) along the pair of guides. Gibbons et al. also disclose the enclosure shaped to receive a key plate (208) parallel to the first plane and intersecting the first guides, said key plate having a plurality of feature areas, each feature area corresponding to a respective plane of one of the pairs of guides, each feature area presenting a predetermined pattern of barriers to movement in the first direction, the barriers disposed at at least two locations (i.e., the front, middle, and back of each feature area) along the first direction. See marked up copy of FIG. 4. Likewise, Gibbons et al. disclose the enclosure further comprising a plurality of electrical connectors corresponding to respective pairs of first and second guides, each connector disposed between ends of its respective first and second guides and positioned perpendicular thereto. See column 4, lines 57-61.

Referring to claim 2, Gibbons et al. disclose a computer system, wherein the key plate (208) is substantially linear and is substantially perpendicular to the first direction. See marked up copy of FIG. 4.

Referring to claim 8, the marked up copy of FIG. 4 of Gibbons et al. shows a key plate (208) comprising a substantially linear member elongated in a first direction (i.e., "x" direction), the key plate having a plurality of feature areas disposed at equally spaced distances along the

Art Unit: 2835

first direction, each feature area presenting a predetermined pattern of barriers to movement in a second direction (i.e., "z" direction) perpendicular to the first direction, the barriers disposed at at least first and second locations along the second direction (i.e., the front, middle, and back of each feature area), and the pattern of barriers being identical in each of the feature areas.

Referring to claim 9, FIG. 2 of Gibbons et al. shows a key plate wherein the number of feature areas (i.e., bays 204) is at least ten.

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claims 3-5, 7, 10 and 11 are rejected under 35 U.S.C. 103(a) as being unpatentable over Gibbons et al. in view of U.S. Patent No. 6,122,173 to Felcman et al. Referring to claim 3, Gibbons et al. disclose a system further comprising a plurality of substantially planar rectangular carriers (206) each having a first rail (302) and a second rail (308) parallel to each other, each carrier shaped for insertion into a pair of first and second guides (216) with the first rail engaged to the first guide and the second rail engaged to the second guide (see FIG. 3 and the corresponding specification). Gibbons does not disclose the first rail of each carrier disposed with protruding pins at at least two locations along its length, and the pins disposed to pass by the predetermined pattern of barriers. Felcman et al. disclose a computer system comprising a hard disk drive (HDD) 84, having pins (90) for insertion into a housing (92). It would have been

Art Unit: 2835

obvious to one of ordinary skill in the art at the time the invention was made to modify the carrier (206) of Gibbons et al. to include the HDD with pins, as taught by Felcman et al., wherein the pins (90) are inserted into notches (506) of the carrier (226) and provide protrusions at at least two locations along the length of the carrier, as an alternate means for attaching the HDD to the carrier.

Referring to claim 4, Gibbons et al. in view of Felcman et al. disclose a substantially planar rectangular carrier (206) carrying a disk drive (502), the carrier having first (302) and second (308) rails parallel to each other, the carrier having an electrical connector along an edge between the first and second rails, the carrier having a handle along the remaining edge (see FIG. 6 of Gibbons et al.). As indicated above, Gibbons et al. in view of Felcman et al. also disclose the first rail having protruding pins at at least first and second locations (506) along its length, with the first location closer to the electrical connector than the second location.

Referring to claims 5, 7, 10 and 11, as best understood by the examiner, Gibbons et al. disclose all of the elements recited in the preamble to the method claims. Specifically, Gibbons et al. disclose a system comprising a carrier (206) and an enclosure (200), the enclosure shaped with a plurality of opposed pairs of first and second guides (216), the first guides all substantially coplanar within a first plane, the second guides all substantially coplanar within a second plane, each pair of guides defining a respective plane (204), the respective planes of the pairs of guides all parallel to each other, each pair of guides separated by a respective spacing, each pair of guides shaped to receive a respective planar carrier (206) by insertion in a first direction ("z" direction of marked up FIG. 4) along the pair of guides, the enclosure shaped to receive a key plate (208) parallel to the first plane and intersecting the first guides, said key plate having a

Art Unit: 2835

plurality of feature areas, each feature area corresponding to a respective plane of one of the pairs of guides, each feature area presenting a predetermined pattern of barriers to movement in the first direction, the barriers disposed at at least third and fourth locations (e.g., the back and front of each feature area) along the first direction, wherein the third location (i.e., the back area) is closer to 'a first connector' than the 'forth location.' Gibbons et al. as disclose the substantially planar rectangular carrier (206) carrying a disk drive (502). See FIGS. 2-4 of and the corresponding specification.

Gibbons et al. also disclose the enclosure (200) further comprising a plurality of first electrical connectors corresponding to respective pairs of first and second guides, each first connector disposed between ends of its respective first and second guides and positioned perpendicular thereto (see column 5, lines 44-47). Likewise, Gibbons et al. disclose the carrier (206) having first (302) and second rails (308) parallel to each other, the carrier having a second electrical connector along an edge between the first and second rails, and a handle along the remaining edge. See FIG. 6 and the corresponding specification.

Gibbons does not disclose the first rail disposed with protruding pins at at least first and second locations along its length, the first location closer to the second electrical connector than the second. However, as indicated above, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the carrier (206) of Gibbons et al. to include a HDD with pins, as taught by Felcman et al., wherein the pins (90) provide protrusions at at least two locations along the length of the carrier (i.e., at a first notch and a second notch (506)), as an alternate means for attaching the HDD to the carrier.

Art Unit: 2835

Regarding claim 5, Gibbons et al. in view of Felcman et al. disclose the method, comprising the steps of inserting the carrier partially into a first pair of guides, while the carrier is being inserted, striking a protruding pin (90a) at the first location (506A) against a barrier at the third location (402), the first and second electrical connectors failing to be in contact. See column 5, lines 50-69.

Regarding claim 7, Gibbons et al. in view of Felcman et al. disclose the method, comprising the steps of inserting the carrier partially into a first pair of guides, and bringing the first and second electrical connectors into contact. See column 5, lines 50-69.

Regarding claim 10, Gibbons et al. in view of Felcman et al. disclose the method, comprising the steps of inserting the carrier partially into a first pair of guides, while the carrier is being inserted, striking a protruding pin (90b) at the second location (506B) against a barrier at the forth location (i.e., the middle or front portion of 208), the first and second electrical connectors failing to be in contact. See column 5, lines 50-69.

Regarding claim 11, Gibbons et al. in view of Felcman et al. disclose the method, comprising the steps of inserting the carrier partially into a first pair of guides, while the carrier is being inserted, striking a protruding pin (90a) at the first location (506A) against a barrier at the forth location (i.e., the middle or front portion of 208), the first and second electrical connectors failing to be in contact. See column 5, lines 50-69.

Conclusion

The prior art made of record and not relied upon is considered pertinent to applicant's disclosure. U.S. Patent No. 6,064,568 to Schmitt discloses a computer system with keying

Art Unit: 2835

mechanism to facilitate placement of carriers in the proper carrier guides, based on the type of

device retained by the carriers.

Any inquiry concerning this communication or earlier communications from the

examiner should be directed to Anthony Q. Edwards whose telephone number is 703-605-4214.

The examiner can normally be reached on M-F (7:30-3:00) First Friday Off.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Darren Schuberg can be reached on (703) 308-4815. The fax phone numbers for the

organization where this application or proceeding is assigned are (703) 308-7722 for regular

communications and (703) 306-5511 for After Final communications.

Any inquiry of a general nature or relating to the status of this application or proceeding

should be directed to the receptionist whose telephone number is (703) 306-9929.

age

May 15, 2003

Page 8

TECHNOLOGY CENTER 2800